

Technical Data Sheet

Patterncoat (21:47- RANGE)

Description

A high-quality quick air-drying finish with a flash point above 25°C, for use as a patterncoat on timber.

Availability

In a full range of colours as shown on our shade cards. Special matchings undertaken if quantities involved are large enough. Available in gloss, semi-matt and matt finish.

Thinners

09:78

Viscosity

Supplied at a viscosity of 40 - 45 secs DIN 6 cup @ 20°C.

Specific Gravity

1.11

Drying

At ambient temperature: Touch dry - 10-15 mins. Print Free - 2-4 hours Hard dry – overnight can also be force dried.



	T .		
as	nr	าก	Int
us		\mathcal{I}	

Above 25°C

Coverage

At a dry film thickness of 25µm coverage will be between 8-10 square metres per litre.

Storage

High flash point outside Highly Flammable Liquids Regulations.

Health and Safety

See Safety Data Sheet.

Application

Substrate must be completely clean and free from contaminants. For spraying material should be thinned to 30/35 secs F4 @ 20°C.

A product Safety Data Sheet should be obtained from Ellsworth Adhesives Ltd prior to use. ATTENTION: Before handling, read product information, Product Safety Data Sheets and container labels for safe use, and any physical and/or health hazard information.

Issue date: 26 September 2019 Ellsworth Adhesives Ltd
Registered Office: 2 Langlands Avenue, Kelvin Business
Park, East Kilbride, Glasgow, G75 0YG, United Kingdom Registered No: 122624
Tel: +44 (0) 1355 231122 Fax: +44 (0) 1355 235266 Website: www.ellsworthadhesives.co.uk